

MAXIMUS-3



UNIVERSAL FIT

ROOF RACK LED LIGHT BRACKET

(Designed to fit Rhino Rack Pioneer Platform)

PART #: UN3004LB

INSTALLATION STEPS

Estimated Install Time: 30 minutes

PLEASE MAKE SURE YOU READ AND UNDERSTAND THE ENTIRE INSTALLATION GUIDE BEFORE YOU START. WE EXPECT YOU TO HAVE BASIC MECHANICAL ABILITIES TO PERFORM THIS INSTALLATION.

WE RECOMMEND THAT YOU SEPARATE AND IDENTIFY ALL THE PARTS AND HARDWARE KITS YOU RECEIVED WITH YOUR SHIPMENT BEFORE YOU PROCEED.



IMPORTANT

Follow these instructions precisely. Maximus-3 is not liable for any damage caused by improperly installed products. It is the purchaser's responsibility to ensure both the installation and maintenance are performed properly as set forth in this guide. We recommend using anti-size paste on all non-thread-lock bolts.

Parts List:

Roof Rack LED Light Brackets

Qty

2

Hardware Kit

M8 x 16 Stainless Steel Bolts

4

M8 Stainless Steel Washers

4

M8 Channel Nut

4

Tools Required:

- Metric Allen Keys Set
- Your basic hand tools

INSTALLATION STEPS

RELOCATE THE SATELITE RADIO ANTENNA

1. Bolt your LED Light Bars onto the Maximus-3 light brackets using the hardware supplied with the lights.
2. Locate your Light Bar Assemblies mount locations on the roof rack as shown.
3. Mount your Light Bars by sliding the channel nuts in the cutout slots in the roof rack and tighten the bolts.
4. Align your Light Bars and tighten all bolts.
5. Use wire connectors and extend the wires and route to the back of the vehicle and to your switch panel.





USE CABLE TIES TO
SECURE WIRE TO
REAR WINDOW HINGE



TUCK WIRE BEHIND
RUBBER SEAL, SLIDE
UNDER AT BOTTOM



ADD A CONNECTOR
HERE AND ROUTE TO
YOUR SWITCH PANEL

Your installation is complete. If you have questions regarding this installation, please contact us at customerservice@maximus-3.com, or call 248-6061745